

EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER : 63086429
PUBLICATION DATE : 16-04-88


APPLICATION DATE : 30-09-86
APPLICATION NUMBER : 61229723

APPLICANT : TOSHIBA CORP;

INVENTOR : KOMANO HARUKI;

INT.CL. : H01L 21/30 G01M 11/00 G01N 21/88
G01R 31/26 H01L 21/30 H01L 21/66

TITLE : STRAIN MEASUREMENT OF X-RAY
MASK



ABSTRACT : PURPOSE: To continuously measure the strain of a mask while X-rays are irradiated onto the mask by a method wherein a holographic image of the same mask at different time, while X-ray are being projected, is recorded by overlapping in a recording medium for waves of the same phase, and the interference fringe generated at the above-mentioned time is analyzed.

CONSTITUTION: The laser beam emitted from a laser beam source 4 is partially reflected by a beam splitter 5, the reflected light 7 is magnified by a lens 9 to a spot diameter which is sufficient for irradiation on the whole surface of the detection region of $B_{12}SiO_{20}$ crystal (BSO) 10, and it is made incident on the BSO 10. The light 6 transmitted through the splitter 5 is introduced into an X-ray irradiation chamber 1, made incident obliquely on an X-ray mask 14, and the reflection waves are made incident at right angles on the BSO 10. At this time, the interference fringe of the holographic image formed by the interference with a reference light is recorded on the BSO 10. When the second holographic image is subjected to fog exposure within the record maintaining time of the BSO crystal, the interference fringe of two holographic images are recorded. The design of the interference fringe appearing on the BSO is scanned by a vidicon 11, and power is outputted to a CRT 12. Also, numerical processing is conducted by a computer 13 to analyze the strain.

COPYRIGHT: (C)1988,JPO&Japio